



$\phi 75 h8 -0.05$
Clamping diameter

$\phi 37.80 h8 -0.04$
Clamping diameter

Phase adjustment

$\phi 43.40$
F-Mount
Flange distance 46.5 mm

$\phi 65$

228.10 185.90 148.41 128.78 86.22 61.58 49.26 31.26 0 4.30

(232.40)

Material		N.A.		Mass		894 g		Scale		1:1				
Surface treatment		N.A.		Part No.		CO71430								
Geometrical tolerance (ISO 2768-2)								Class	K	Description				
Linear tolerance (ISO 2768-2)								Class	m	Undimensioned bevels	0.5x45°			
0.5	>3±	>6±	>30±	>120	>400±	>1000	>2000	Undimensioned radii	R 0.5	TC4MHR048-F				
±3	6	30	120	±400	±1000	±2000	±4000			Drawing No.				
±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2			Sheet				
<p>OPTO ENGINEERING S.r.l. - Mantova, Italy - Tel. +39 0376699111 - www.opto-e.com</p>								Date	Name		Drawing No.		Sheet	
								Designed	04/04/2014	Vasconetto		DP 71430-C		1/1
								Drawn	05/06/2014	Rodella				
								Checked						
<p>Secret and confidential - All rights reserved - No copy, dissemination or circulation is allowed unless specifically authorized in writing by OPTO ENGINEERING S.r.l. - Any violation shall be legally prosecuted.</p>														

all dimensions are in mm